



# PROCOR CHEMICALS, INC.

## Technical Data Sheet PRO Wash™



### DESCRIPTION

**PRO Wash™** is a blend of selected ionic and anionic surfactants with a variety of uses ranging from general rig and engine cleanup to specialized cuttings wash solutions for oil muds. This multipurpose product is especially effective as a rig wash for general cleaning when using oil-base mud. **PRO Wash™** is also an effective flushing agent during riser flush operations. **PRO Wash™** is a heavy duty detergent and degreaser, which makes those tough cleanup jobs easier. **PRO Wash™** is effective in both freshwater and seawater.

### TYPICAL PROPERTIES

<b>Appearance</b>	Bue liquid
<b>Ionic Character</b>	Ionic/Anionic
<b>Specific Gravity</b>	1.02
<b>ph (1% Solution)</b>	8.3
<b>Flash Point</b>	None
<b>LC 50 Testing</b>	PPM: >298,224 = 0.1, Pass

### APPLICATIONS

Apply <b>PRO Wash™</b> as a rig and equipment wash when using oil-base muds.
Apply <b>PRO Wash™</b> as a cuttings wash solution when using oil-base muds.
Apply <b>PRO Wash™</b> to emulsify oil in water in the treatment of minor oil spills.
Apply <b>PRO Wash™</b> as a cleaning solution for all wood, plastic and metal surfaces.
Apply <b>PRO Wash™</b> as a riser flushing agent.

### TYPICAL USE RATES

For use as a general rig and engine degreaser, regardless of mud type, apply full-strength or dilute with water as needed.
As a cuttings wash solution when using oil-base muds, the recommended concent ration is a 2 to 3% solution (i.e., 2 to 3 gal of CLEAN UP detergent per 100 gal of water).
All oil spills should be treated in a manner which complies with applicable environmental regulations.
As a cleaning solution for all wood, plastic and metal surfaces, dilute <b>PRO Wash™</b> with water as required.
As a riser flushing agent apply PRO Wash full strength.

### PACKAGING

10% to concentrated pills. <b>PRO Wash™</b> is packaged in 5 gal bkts. (36 bkts. per pallet)/ 55 gal drums/ 275 gal. tote tanks.
--